## Claim Set as Amended

1. (Currently Amended) In an image communication apparatus for compressing video and audio data of an image and transmitting them, a packet data transmission protocol, in which one packet data frame comprises:

header data containing information for separating video data and audio data and for synchronizing between a transmitter side and a receiver side;

transmission and reception data size information based on a communication speed;

compressed audio data and video data;

a control index representing information for indicating an additional operation including an image quality selection, an image retransmission, a privacy mode and a change in the size of video data; and

control data for notifying a the receiver side of data relating to the additional operation, for representing information for requesting a compression ratio of the video data to be transmitted when the control index is controlled to select the quality of the image, and for representing a sequence number for requesting the image retransmission when the retransmission of the image data is requested in the control index.

2-7. (Deleted)

Application No.: 09/764,064 Attorney Docket No. 0630-1221P Art Unit 2613 Amendment filed June 23, 2004

Page 3

8. (Currently Amended) The data transmission protocol according to claim-6 1, wherein the control data represents the information of a packet size (SN+CRC+DATA) of the image data when the control index represents a change

in the image data size.

9. (Currently Amended) The data transmission protocol according to claim 3 1, wherein the privacy mode is an information for representing the an

inverse of video or audio data and the a reverse of video or audio data.

10. (Original) The data transmission protocol according to claim 9, wherein, in the privacy mode, the video or audio data is transmitted in the inverse or reverse state according to the above information control data and the

control index.

11. (Currently Amended) The data transmission protocol according to claim—3 1, wherein, in the image data size,—a the sequence number and a Cyclic Redundancy Checking (CRC) code are inserted for each different image data size based on a predetermined value according to the change in the image data

size indicated by the control index information.

12. (Original) The data transmission protocol according to claim 11, wherein, when the data size is less than 15 Kbytes, the sequence number and

the CRC are inserted for every 64 bytes or 128 bytes.

13. (Original) The data transmission protocol according to claim 11, wherein, when the data size is more than 15 Kbytes, the sequence number and

Application No.: 09/764,064 Art Unit 2613

Attorney Docket No. 0630-1221P Amendment filed June 23, 2004

Page 4

the CRC are inserted for every 256 bytes or 2048bytes.

14-19. (Deleted)